

## TECHNICAL DATA SHEET OPERATING TABLE ST5

Manufacturer	Sordina S.r.l
Model	ST5
CND Code	Z12011202
RDM Code	1732547
Release on the market of the latest version (year)	2016
Intended Use	The Operating Table ST5 is designed to be used in operating rooms and for medical purposes, according to current legislation, to perform operations of all surgical specialties. The Operating Table ST5 is intended to be used in public and private healthcare environment and by personnel trained and authorized by the user (responsible authority). The Operating Table ST5 is suitable for adult patients.
Materials	
Base	Stainless Steel
Coloumn	Stainless Steel
Table	Stainless Steel
Lateral Rails for accessories	Stainless Steel (mis. 25 x 10 mm, standard in compliance with current European legislation). Rails are present for the whole length of the operating table.
Mattress	Mattresses in foamed polyurethane, radiolucent, free from latex, with antistatic treatment (in compliance with current European legislation).  Mats covered in waterproof material and resistant to trauma, easily removable for disinfection and cleaning. Innovative ergonomic shape designed for antidecubitus.
Table Width	570 mm (external rails) - 520 mm (interal rails)
Table Lenght	2020 mm
Loading Capacity	297 Kg
Power supply	Power supply by batteries and electricity Power supply:  □ Voltage: 110/220 V  □ Frequency: 50/60 Hz □ Power: 260VA
Battery type and autonomy	2 batteries in Pb series 12V-12Ah, incorporated in the base and rechargeable, without memory effect and maintenance necessity.

## Sordina S.r.l.

Capital € 10.000,00

P. IVA e C.F: 02978720593 - REA LT 214450 e-Mail: <u>info@sordina.com</u>-web: <u>www.sordina.com</u>

## **Administrative Office**

Galleria del Pozzo Rosso nr.13 - 36100 Vicenza, Italy Tel. +39 0444 233750 – Fax +39 0444 233790 Registered Office and Operating Office Via dell'Industria 1/A - 04011 Aprilia (LT), Italy

Tel. +39 06 92730650

	Automatic recharge activation in case of
	connection to the network.
	□ Normal charging time: 8 hours
	☐ Battery autonomy: 60 minutes
Base features	Mobile type base on wheels, equipped with an
	innovative electrically operated floor locking
	system (electro-hydraulic locking).
	-,
	Automatic operating table locking system on the
	floor operated by remote control.
	Wheels made of materials and dimensions that
	ensure maximum mobility and safety, the absence
	of prints on the antistatic floors of the operating
	rooms and make the movement of the Operating
	Table easier.
Coupling sections	Coupling of the different sections of the operating
	table through an innovative lock-unlock system.
	The new system makes the assembly and
	disassembly of the various sections of the operating
	table extremely simple and fast.
Automatic electro-hydraulic movements of the	Height Variation: 680-940 mm
operating table	Trendelemburg-Reverse: + 30 ° / -30 °
	Lateral tilt (Tilt): + 20 ° / -20 °
	Backrest Adjustment: + 75 ° / -25 °
	Longitudinal translation: 300 mm
Manual movemebts of the Operating Table	Head Angle (Double-Joint): + 30 ° / -45 °
	Kidney Bridge: 136 mm
	Opening legs: 180 °
	Leg Section Adjustment: 5 ° / 90 °
Movement command	Remote control with cable
Battery status indicators	Real-time indication of battery charge status with
	LED indicator on the remote control.
Controls and protection devices	On the base there is a connector for the connection
	to the equipotential node.
	Coupling of the sections of the Operating Table
	through an innovative lock / unlock system which
	makes the assembly and disassembly of the
	sections of the Operating sections extremely safe,
	simple and fast.
Easy disinfection and washing	Washing with traditional water spray systems.

## Sordina S.r.l.

Capital € 10.000,00

P. IVA e C.F: 02978720593 - REA LT 214450 e-Mail: <u>info@sordina.com</u>-web: <u>www.sordina.com</u>

# SORDINA

	Waterproof and easily removable pillows for
	disinfection and cleaning.
CE Marking	Yes, according to 93/42 / CE directive
	The manufacturer is certified according to the UNI
	EN ISO 9001 and UNI CEI EN ISO 13485
	standards for the design, production, marketing,
	technical assistance and installation of operating
	tables with accessories.
Degree of protection against liquids penetration	IPX 4
Degree of protection against ignition risks of	AP
flammable anesthetic mixtures	

## Sordina S.r.l.

Capital € 10.000,00

P. IVA e C.F: 02978720593 - REA LT 214450 e-Mail: <u>info@sordina.com</u>-web: <u>www.sordina.com</u>

## **Administrative Office**

Galleria del Pozzo Rosso nr.13 - 36100 Vicenza, Italy Tel. +39 0444 233750 – Fax +39 0444 233790 Registered Office and Operating Office Via dell'Industria 1/A - 04011 Aprilia (LT), Italy Tel. +39 06 92730650